

Product Code	VLT%	UV%	IR%	SRC Rate	Layer	Thickness	Total Solar Energy Rejected
CR5070	70	99	50	3H	1-ply	37.5u (1.5mil)	48

Product Code	VLT%	UV%	IR%	SRC Rate	Layer	Thickness	Total Solar Energy Rejected
CR6060	62	99	60	3H	1-ply	37.5u (1.5mil)	58

Terminology

T%: Transmittance Rate

R%: Reflectance + Absorptance Rate

IR: Infrared (Solar Heat) in spectrum range >700nm.

UV: Ultraviolet in spectrum range <400nm.

Visible Light: Spectrum range 401nm~699nm.

Specification Tolerance: ±5%.

SRC: Scratch Resistance Hardcoat.

IRISFILM Corp.

Taipei Regional Office

3F, No. 208, Shi-Tsang Road, Taipei City 10861, Taiwan R.O.C.

No. 69, Dinghu Road, Takang Gueishan Shiang,

Taoyuan County, 33378 Taiwan R.O.C.

Tel: +886-2-2302-3000 (Operator)

Sales Direct Line: +886.2.2336.7198

Fax: +886-2-2302-4000

E-mail: sales@irisfilm.com.tw

Web: <http://www.irisfilm.tw>

Business Hours 9:00 am ~ 6:00 pm (GMT + 8:00 Taipei Time)