

Supreme Clear series are coated with nanotech materials, providing crystal clear views and great visible transmittance rate, plus up to 10 years color stable and bubbling warranties.



***SCA Series: 10 Years Warranty**

Product Code	VLT%	UV%	IR%	SRC Rate	Layer	Thickness	Total Solar Energy Rejected
SCA1603	50	99	50	4H	1-ply	38u(1.52mil)	51.5
SCA1604	50	99	50	4H	1-ply	38u(1.52mil)	51.5
SCA1607	55	99	50	4H	1-ply	38u(1.52mil)	49.3
SCA1608	20	99	80	4H	1-ply	38u(1.52mil)	80.6



***SCB Series: 5 Years Warranty**

Product Code	VLT%	UV%	IR%	SRC Rate	Layer	Thickness	Total Solar Energy Rejected
SCB109	55	99	50	4H	2-ply	43u(1.72mil)	49.3
SCB110	60	99	50	4H	2-ply	43u(1.72mil)	47.2
SCB115	55	99	50	4H	2-ply	43u(1.72mil)	49.3
SCB116	50	99	60	4H	2-ply	43u(1.72mil)	56.9
SCB117	45	99	50	4H	2-ply	43u(1.72mil)	53.6



***SCC Series: 3 Years Warranty**

Product Code	VLT%	UV%	IR%	SRC Rate	Layer	Thickness	Total Solar Energy Rejected
SCC803	40	99	65	4H	2-ply	43u(1.72mil)	47.7
SCC804	30	99	65	4H	2-ply	43u(1.72mil)	68.2
SCC805	10	99	50	4H	2-ply	43u(1.72mil)	68.7
SCC806	15	99	65	4H	2-ply	43u(1.72mil)	74.6
SCC808	15	99	50	4H	2-ply	43u(1.72mil)	66.5
SCC810	30	99	65	4H	2-ply	43u(1.72mil)	68.2
SCC817	5	99	65	4H	2-ply	43u(1.72mil)	66
SCC818	35	99	65	4H	2-ply	43u(1.72mil)	66
SCC819	35	99	65	4H	2-ply	43u(1.72mil)	66
SCC825	52	85	45	4H	2-ply	43u(1.72mil)	40

Terminology

T%: Transmittance Rate

R%: Reflectance + Absorptance Rate

IR: Infrared (Solar Heat) in spectrum range >700nm.

UV: Ultraviolet in spectrum range <400nm.

Visible Light: Spectrum range 401nm~699nm.

Specification Tolerance: ±5%.

SRC: Scratch Resistance Hardcoat.

IRISFILM Corp.

Taipei Regional Office

3F, No. 208, Shi-Tsang Road, Taipei City 10861, Taiwan R.O.C.

No. 69, Dinghu Road, Takang Gueishan Shiang,

Taoyuan County, 33378 Taiwan R.O.C.

Tel: +886-2-2302-3000 (Operator)

Sales Direct Line: +886.2.2336.7198

Fax: +886-2-2302-4000

E-mail: sales@irisfilm.com.tw

Web: <http://www.irisfilm.tw>

Business Hours 9:00 am ~ 6:00 pm (GMT + 8:00 Taipei Time)